

QUESTIONS & ANSWERS

Kill your exam at first Attempt



Intel

ILO-786

Designing Flexible Wireless LAN Solutions

QUESTION: 65

A customer has a DHCP server on the network and wants the Intel PRO/Wireless Access Point to be automatically assigned an IP address from this server. What must you do to allow this capability on a new installation?

- A. You use the serial interface and enable DHCP.
- B. You first assign a static IP and then reboot the Access Point to enable DHCP.
- C. No configuration is required. DHCP is the default configuration.
- D. There is nothing you can do. DHCP is not supported on the Access Point.

Answer: C

QUESTION: 66

Which three attenuate RF signals the most? (Choose three.)

- A. metal
- B. plaster
- C. concrete
- D. paper rolls

Answer: A,C,D

QUESTION: 67

What is WEP?

- A. Wired Equivalent Privacy
- B. Windows Equivalent Privacy
- C. Wireless Equivalent Privacy
- D. Windows Equivalent Protection

Answer: A

QUESTION: 68

Wireless infrastructure networking requires which two parameters? (Choose two.)

- A. ESS ID
- B. hop sequence
- C. encryption level
- D. access control list

Answer: A,C

QUESTION: 69

What is the first level of security encountered when managing an AP?

- A. ESSID
- B. 40-bit encryption
- C. 128-bit encryption
- D. system password

Answer: D

QUESTION: 70

What are two methods of loading an ACL on an AP? (Choose two.)

- A. load an ACL from a file using Xmodem
- B. Telnet to the AP, then load an ACL file
- C. manually enter individual MAC addresses
- D. manually enter a range of MAC addresses

Answer: C,D

QUESTION: 71

KILLEXAMS.COM

Given:

MobileUnit 1 and MobileUnit 2 are out of range of each other. MobileUnit 1 and MobileUnit 2 transmit at the same time and a collision occurs. What is this issue called?

- A. multipath
- B. skin effect
- C. hidden node problem
- D. Differentiated Inter-Frequency Stability

Answer: C

QUESTION: 72

What do the periods in front of certain configuration options indicate?

- A. The option can be saved to all APs with the same subnet.
- B. The option can be saved to all APs with the same ESSID.
- C. The option can be saved to all APs on the same subnet and same firmware revision.
- D. The option can be saved to all APs with the same ESSID and same firmware revision.

Answer: D

QUESTION: 73

What are two ways to deny access to a network through an AP? (Choose two.)

- A. ACL
- B. CCA
- C. ESSID
- D. APID

Answer: A,C

KILLEXAMS.COM

For More exams visit <http://killexams.com> -



KILLEXAMS.COM

Kill your exam at First Attempt....Guaranteed!